

UPC Number

Material Safety Data Sheet

Product Name DDOEECCIONAL EACY OFF® OVEN 9			
PROFESSIONAL EASY-OFF® OVEN & GRILL CLEANER (READY-TO-USE)	MSDS#	Not available.	
Not available.	Validation Dat	e 22 August 2008	
	Print Date	22 August 2008	
Reckitt Benckiser North America, Inc. Morris Corporate Center IV 399 Interpace Parkway (P.O. Box 225) Parsippany, N.J. 07054-0225	In case of Emergency:	Telephone: 800-677-9218 (Professional Products)	
Not available.	Transportation	Chambras 1 200 424 0200	
358467	Emergencies:	Chemtrec: 1-800-424-9300 (U.S. & Canada)	
		Outside the U.S & Canada (North America), call: 703-527-3887	
	Reckitt Benckiser North America, Inc. Morris Corporate Center IV 399 Interpace Parkway (P.O. Box 225) Parsippany, N.J. 07054-0225 Not available.	Reckitt Benckiser North America, Inc. Morris Corporate Center IV 399 Interpace Parkway (P.O. Box 225) Parsippany, N.J. 07054-0225 Not available. Transportation Emergencies	

Section 2. Composition and Information on Ingredients			
Name	CAS#	% by Weight	Exposure Limits : TLV/PEL
1) SODIUM METASILICATE 2) POTASSIUM HYDROXIDE	6834-92-0 1310-58-3	2.0 <5.0	Not available. CEIL: 2 (mg/m³) from ACGIH (TLV) [United States]

36241-80689 (64 oz); 62338-74377 (1 gallon)

Section 3. Hazards lo	dentification	
Emergency Overview	DANGER: Corrosive. Causes burns to eyes and skin on contact. Harmful if swallowed. KEE REACH OF CHILDREN!	EP OUT OF

Section 4. First Aid Measures		
Eye Contact	Immediately flush eyes thoroughly with water, remove any contact lenses and continue to flush eyes with plenty of water for at least 15 minutes. Get medical attention.	
Skin Contact	Immediately flush thoroughly with plenty of water for 10 minutes. If irritation persists, get medical attention,	
Inhalation	If affected by inhalation, remove to fresh air. Call a physician or poison control center as necessary.	
Ingestion	Do not induce vomiting. Give several glasses of water to dilute the product. Call a physician or poison control center immediately. NEVER give an unconscious person anything to ingest.	

Section 5. Fire and Explosion Data	
Flammability	Not flammable. See Section 14 for any Shipping Classifications.
Flash Point	CLOSED CUP: Higher than 93.3°C (>200°F). (Tagliabue).
Explosive Limits in Air	Not available.
Products of Combustion	Not available.

Continued on Next Page

PROFESSIONAL EASY-OFF® OVEN & Page Number: 2 GRILL CLEANER (READY-TO-USE)		
Fire and Explosion Hazards		
Fire Fighting Media and Instructions	Use water spray, foam, dry chemical or carbon dioxide, as suitable for the surrounding fire.	
Special Fire Fighting Instructions	Wear self-contained breathing apparatus and protective clothing appropriate for fighting a typical chemic	cal fire.

Section 6. Accidental Release Measures	
Accidental Spill	Small spills: Wearing rubber gloves, spill should be wiped up with inert absorbent material and disposed of in a suitable waste container. The residue should be rinsed or flushed to the sink or sanitary sewer.
	Large spills: Wearing appropriate personal protective equipment, the spill of concentrated material should be contained, collected and evaluated for disposal according to state and federal hazardous waste regulations. Undiluted or concentrated material SHOULD NOT be flushed to sewer.

Section 7. Handling and Storage		
Handling and Storage	DANGER: Corrosive. Causes burns to eyes and skin on contact. Harmful if swallowed. Contains potassium hydroxide and sodium metasilicate. Do not take internally. Do not get in eyes, on skin, on mucous membranes or on clothing. Wear eye protection and long rubber gloves when handling. Avoid breathing spray mist. If clothing is contaminated, remove and wash clothing before reuse. Store in original container in area inaccessable to small children and pets. KEEP OUT OF REACH OF CHILDREN.	

Section 8. Exposure Controls/Personal Protection		
Ventilation Requirements	None required.	
Eye Protection	Wear eye protection when handling. Emergency responders should wear full eye and face protection.	
Skin Protection	Wear long rubber gloves when handling. Emergency responders should wear impermeable gloves.	
Respiratory Protection	Avoid breathing spray mist.	
Other Protection	Emergency responders should wear impermeable clothing and footwear when responding to a situation where contact with the liquid is possible.	
Work/Hygienic Practices	Remove and wash any contaminated clothing and clean contaminated shoes before reuse. Wash thoroughly with soap and water after handling.	

Description	Thick, opalescent, clear ∨iscous liquid.	Odor	Characteristic chemical odor (Glycol ether).
pН	14 [Basic.]	Color	Colorless.
Boiling/Condensation Point	Not determined.		
Specific Gravity	Not available.		
Vapor Pressure	Not determined.		
Vapor Density	Not available.		
Viscosity	Not available.		
Solubility	Complete		
Physical Chemical Comments	Not available.		

Continued on Next Page

Section 10. Stability and Reactivity Data		
Chemical Stability	The product is stable.	
Conditions of Instability	None known.	
Incompatibility with Various Substances	Do not mix with acids and oxidizers.	
Hazardous Decomposition Products	None known.	
Hazardous Polymerization	Will not occur.	

Section 11. Toxicological Information		
Exposure effects		
Eye Contact	Corrosive. Causes burns to eyes on contact.	
Skin Contact	Corrosive. Causes burns to skin and mucous membranes on contact.	
Inhalation	Corrosive. Avoid breathing spray mist.	
Ingestion	Corrosive. Harmful if swallowed.	
Carcinogenicity	Not listed as carcinogenic by OSHA, NTP or IARC.	

Section 12. Ecological Information		
Ecotoxicity	Not available. Do not allow any spilled material to enter a stream, brook, river, pond, lake or any other waterway to prevent injury to wildlife.	

Section 13. Disposal Considerations		
Waste Disposal	For small amount of liquid waste, discard absorbed material in trash collection or dilute liquid with large quantity of water and flush to sanitary sewer.	
	For large amounts of waste product: Contain and collect liquid for evaluation and disposal according to local, state and federal regulations.	

DOT Classification	Corrosive Liquid, basic, inorganic, N.O.S. (Contains Potassium Hydroxide, Sodium Metasilicate), Class 8, UN 3266, PG II.	CHEGOSIVE	
Proper Shipping Name	Corrosive liquid, basic, inorganic, n.o.s. (contains Potassium Hydroxide, Sodium Metasilicate)		
DOT Identification Number	UN3266		
Packing Group			
Maritime Transportation	Not available.		
Hazardous Substances Reportable Quantity	Not available.		
Special Provisions for Transport	UN Performance packaging required.		

Continued on Next Page

	EASY-OFF® OVEN & Page Number: 4 (READY-TO-USE)	ſ
TDG Classification	Corrosive liquid, basic, inorganic, n.o.s. (contains Potassium Hydroxide, Sodium Metasilicate) Class 8, UN3. PG II	266,
ADR Classification	Not available.	
IMDG Classification	Corrosive liquid, basic, inorganic, n.o.s. (contains Potassium Hydroxide, Sodium Metasilicate) Class 8, UN3. PG II	266,
IATA Classification	DO NOT SHIP! - Packaging does not meet IATA requirements.	

Section 15. Regulatory Information Federal and State Regulations SARA Title III, Section 313 Toxic Chemical Notification & Release Reporting: None California Proposition 65: This product contains the following ingredients which require a warning under the Safe Drinking Water & Toxic Enforcement Act:

Other Classifications WHMIS (Canada) CLASS D-1B: Material causing immediate and serious toxic effects (TOXIC). CLASS E: Corrosive liquid.

New Jersey Right-To-Know Regulation: WATER CAS #: 7732-18-5

POTASSIUM HYDROXIDE CAS #: 1310-58-3


TRIPROPYLENE GLYCOL METHYL ETHER CAS #: 25498-49-1

SODIUM METASILICATE CAS #: 6834-92-0

ACRYLIC COPOLYMER CAS #: N/A

Section 16. Other Information

HMIS (U.S.A.)



National Fire Protection Association (U.S.A.)

Health



Not applicable.

Updated by Regulatory on 8/22/08 to include new 64 oz size

Printed: 22 August 2008

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.